АИА•М

Description for Catalog Number: 7470-10 Printed 12/31/2013 6:59:24 PM Page 1 of 1

Corning Incorporated Life Sciences

<u>Registered</u> ISO 9001:2008 Product Description

Catalog Number: 7470-10

Product Description: PYREX® Stopcock Two-Way, In-Line, Plain Bore, 0-10 mm, with Rotary PTFE High Performance Plug

Component Materials:

 Glass - Type I Class A - Low-Expansion Borosilicate Glass, per ASTM E438 (Standard Specification for Glasses in Laboratory Apparatus)
Plug - Polytetrafluoroethylene (PTFE)

Attributes:

Product Dimensions - 13 mm Sidearm OD x 224 mm Total Length

Autoclaving:

This product will withstand repeated standard autoclave cycles of 121°C at 15 psi for 15 minutes.

Heating / Cooling:

This product should NOT be heated while being used in a vacuum or pressure application as the combination of thermal and mechanical stresses could cause a failure.

This product is not designed for freezing applications.

Vacuum / Pressure:

This product is rated for vacuum applications.down to 10⁻⁶ torr (0.000001 mm of Mercury at 0 degrees C).

This product can be used at pressure up to 100 psi. We CANNOT offer any information as to suitablility or limits on the products attached to this product.

Sterilization: Shipped Not Sterile

Lot Number Designation:

Each production lot is uniquely identified with an 8 digit lot number as follows: First 3 digits - Julian date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Revision Date: 14 AUG 2013

Rev No: 1

